



G. L. € Paints
دهانات جي.إل. إي

Technical Product Specifications Pro - Shield

Water Based Paints

PRODUCT DESCRIPTION

Transparent protection insulator, manufactured using 100% pure polymer acrylic high quality that can be applied to external facades to give a smooth layer of protection .

PRODUCT CHARACTERISTICS

- Transparent insulation.
- Dilution with water in the amount of a more.
- Excellent resistance to water vapor and alkali.
- Excellent resistance to weather factors.

RECOMMENDED USE

Suits indoor and outdoor applications.

TYPE OF SURFACE

Concrete, Cement Plaster & Bathrooms...etc.

TECHNICAL SPECIFICATION

Final Appearance	Matt - gloss - Semi-gloss
Viscosity	95 ± 5 Kreps (at 25°C temperature and 50% humidity) according to (ASTM D5622014) 10-)
Density	1.00 ± 0.05 gm/cm ³ (at 25°C temperature and %50 humidity). according to (ASTM D13-1475)
Solids by Volume	20 ± 2%
Flash Point	Non inflammable

METHOD OF APPLICATION

Diluent	Water
% Dilution (by volume)	10% - 15
Tools	Roller, Brush, Sprayer

FILM THICKNESS AND SPREADING RATE

	Min. Thickness	Max. Thickness	Average
Dry Film Thickness in Micron	25	35	27.5
Non-Dry Film Thickness in Micron	125	150	137.5
Theoretical Spreading Rate (m ² /liter)	8	6	7.27



G . L . € Paints
دهانات جي . إل . إي

Technical Product Specifications Pro - Shield

Water Based Paints

DRYING TIME

Generally, drying time depends on air draft, temperature, film thickness, selected colors, and number of coats.
Data in schedule is measured at °25C temperature and %50 humidity .

Surface Drying (for white color)	2 hours approximately
Re-coating (for white color)	5 hours approximately
Full Dry	24 hours

RECOMMENDED COATING SYSTEM

All surfaces (new and old) should be clean and free from dust, oil, fat...etc.

FOR NEW SUBSTRATES

- Application of 1st. Coat Pro - Shield

FOR OLD SURFACES

- After sandpapering, clean the surface properly with suitable detergent and water.
Let dry, then follow the steps for application.
- Application of 1st. Coat Pro - Shield.

CONDITIONS OF APPLICATION

- Temperature of surface to be painted should not be lower than °10C and °3C above dew point.
Appropriate air temperature and humidity should be observed.

GENERAL NOTES

- 1 Actual spreading rate depends on many factors like surface condition, effectiveness of application tool, film thickness, surface porosity, surface defects, temperature and quantity lost during application...etc.
- 2 - Maximum spreading rate for one coat may be realized by minimizing the dry film thickness, and vice versa.
- 3 - Paint should be mixed before use if it is made of different batches.

STORAGE

- Two years from the date of production, provided that appropriate storage conditions are observed .
- The product should be stored in a cool, well-ventilated place away from sunlight and direct heat .
- Containers must be tightly closed after use .



G . L . € Paints
دهانات جي .إل . إي

Technical Product Specifications Pro - Shield

Water Based Paints

Instructions for use and safety

- Please read and follow the health and safety instructions on the package .
- The product must be handled with caution before and during application .
- Avoid contact of the paint with the eyes and skin or inhale its spray and vapors during application .
- It is advisable to use the product in well-ventilated places or use artificial ventilation when applying with a spray .
- Keep out of reach of children .

SAFETY BREATHING APPARATUS

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

HAND PROTECTION

Protective creams may be used for exposed skin, but they should not be applied after contact with the product. In the event of the prolonged or repeated contact with the hands, use appropriate gloves.

EYE AND FACE PROTECTION

Use eye protectors designed to protect against liquid splashes.

For the safety of the environment:

Please hand over the waste paint and surplus packaging to any local authorized authority for the purpose of use or recycling.

CLARIFICATION

The information in this Technical Specification is given to the best of our knowledge.

It is based on laboratory tests and practical experience.

Golden line paints & putty company takes no responsibility for consequences of breaching the instructions.

The Company reserves the right to change data herein without notice. Version: 2024, Golden Line paints & putty company.

This version supersedes prior versions .



G . L . € Paints
دهانات جي .إل . إي

Kingdom of Saudi Arabia - Riyadh - Tel : 0553201818 - 0112987774

For more information email us at : info@glepaints.com Or sales@glepaints.com

www.glepaints.com