



G . L . € Paints  
دهانات جي . إل . إي

## Technical Product Specifications Epoxy Zinc Rich

### PRODUCT DESCRIPTION

High-build final epoxy primer paint resistant to corrosion and rust for iron and steel, consisting of two components containing solvents, based on epoxy resin and a special amino hardener, with pigments of zinc phosphate.

### RECOMMENDED USE

- Painting all types of iron and metalworks.
- Painting high voltage electricity towers and hangar iron.
- Treating and protecting reinforced concrete iron from rust.
- Painting road facilities, bridges, and water and sewage stations.
- Painting tanks, pipes, machines, and metal structures exposed to chemical effects.

### TECHNICAL SPECIFICATION

Color	Gray - White and other colors
Density	1.25 ± 0.05 kg/L (at 25°C temperature and %50 humidity). according to (ASTM D13-1475)
Mixing ratio	8.1 A : 1.25 B
Solids by Volume	75 %
Operating time	3 Hours

### Application method:

Thinner: Thinner

Application tools: Roller, Spray Gun, Brush.

Drying time: Surface dry: 2 hours (minimum)

Complete dry: 10 hours (minimum).

### STORAGE

- Two years from the date of production, provided that appropriate storage conditions are observed .
- The product should be stored in a cool, well-ventilated place away from sunlight and direct heat .
- Containers must be tightly closed after use .

### Instructions for use and safety

- Please read and follow the health and safety instructions on the package .
- The product must be handled with caution before and during application .
- Avoid contact of the paint with the eyes and skin or inhale its spray and vapors during application .
- It is advisable to use the product in well-ventilated places or use artificial ventilation when applying with a spray .
- Keep out of reach of children .

### For the safety of the environment:

Please hand over the waste paint and surplus packaging to any local authorized authority for the purpose of use or recycling.

### CLARIFICATION

The information in this Technical Specification is given to the best of our knowledge.

It is based on laboratory tests and practical experience.

Golden line paints & putty company takes no responsibility for consequences of breaching the instructions.

The Company reserves the right to change data herein without notice. Version: 2024, Golden Line paints & putty company.

This version supersedes prior versions .



G . L . € Paints  
دهانات جي . إل . إي

Kingdom of Saudi Arabia - Riyadh - Tel : 0553201818 - 0112987774

For more information email us at : [info@glepaints.com](mailto:info@glepaints.com) Or [sales@glepaints.com](mailto:sales@glepaints.com)

[www.glepaints.com](http://www.glepaints.com)