



G . L . € Paints
دهانات جي . إل . إي

Technical Product Specifications

Crystal Rock

PRODUCT DESCRIPTION

High-quality water-based paint. Made from %100 pure acrylic copolymer emulsion and contains coarse granules to give a luxurious stone-like appearance.

PRODUCT CHARACTERISTICS

- Extremely easy to apply.
- High adhesion strength.
- Features a unique architectural appearance inspired by travertine rocks.
- Contains coarse grains that give it a luxurious stone touch.
- Its authentic stone look and distinctive texture make it the perfect finishing touch for both modern and traditional homes.

RECOMMENDED USE

- Suitable for outdoor use.

TYPE OF SURFACE

Concrete, Cementitious, and Gypsum surfaces, etc.

TECHNICAL SPECIFICATION

Final Appearance	stone
color	Multiple colors
Viscosity	250 ± 10 Kreps (at 25°C temperature and %50 humidity) according to (ASTM D(2014) 10-562)
Density	1.70 ± 0.05 gm/cm ³ (at 25°C temperature and %50 humidity). according to (ASTM D13-1475)
Solids by Volume	%2 ± 57
Flash Point	Non inflammable

METHOD OF APPLICATION

Diluent	water
% Dilution (by volume)	(10 - 15%)
Tools	Spatula - Knife

FILM THICKNESS AND SPREADING RATE

The rate per individual depends on the thickness of the applied layer, the type of texture, the porosity of the surface, defects, temperature, waste during painting, etc. The paint requirement ranges from **0.8 to 1 kg/m²**.



G. L. € Paints
دهانات جي.إل.إي

Technical Product Specifications Crystal Rock

DRYING TIME

Generally, drying time depends on air draft, temperature, film thickness, selected colors, and number of coats.
Data in schedule is measured at 25°C temperature and %50 humidity .

Surface Drying	3 hours approximately
Re-coating	3 hours approximately

RECOMMENDED COATING SYSTEM

All surfaces (new and old) should be clean and free from dust, oil, fat...etc.

FOR NEW CEMENTITIOUS, CONCRETE AND GYPSUM SURFACES

- 1 Coat Primer G - 101 .
- 2 Coat Crystal Rock .

FOR OLD SURFACES

- After sandpapering, clean the surface properly with suitable detergent and water.
- 2 Coat Crystal Rock.

CONDITIONS OF APPLICATION

- Temperature of surface to be painted should not be lower than 10°C and 3°C above dew point.

Appropriate air temperature and humidity should be observed.

GENERAL NOTES

- 1 Actual spreading rate depends on many factors like surface condition, effectiveness of application tool, film thickness, surface porosity, surface defects, temperature and quantity lost during application...etc.
- 2 - Maximum spreading rate for one coat may be realized by minimizing the dry film thickness, and vice versa.
- 3 - Paint should be mixed before use if it is made of different batches.

STORAGE

- Two years from the date of production, provided that appropriate storage conditions are observed .
- The product should be stored in a cool, well-ventilated place away from sunlight and direct heat .
- Containers must be tightly closed after use .

Instructions for use and safety

- Please read and follow the health and safety instructions on the package .
- The product must be handled with caution before and during application .
- Avoid contact of the paint with the eyes and skin or inhale its spray and vapors during application .
- It is advisable to use the product in well-ventilated places or use artificial ventilation when applying with a spray .
- Keep out of reach of children .

For the safety of the environment:

Please hand over the waste paint and surplus packaging to any local authorized authority for the purpose of use or recycling.

CLARIFICATION

The information in this Technical Specification is given to the best of our knowledge.

It is based on laboratory tests and practical experience.

Golden line paints & putty company takes no responsibility for consequences of breaching the instructions.

The Company reserves the right to change data herein without notice. Version: 2024, Golden Line paints & putty company.

This version supersedes prior versions



G. L. € Paints
دهانات جي.إل.إي

Kingdom of Saudi Arabia - Riyadh - Tel : 0553201818 - 0112987774
For more information email us at : info@glepaints.com Or sales@glepaints.com
www.glepaints.com